



EWFF POWER PACKS

Excavators



Dozers



Graders



Loaders



Ag Tractors



Reach Top-Level Productivity with Dedicated Extra Power for your Hydraulic Attachments

Compact design and straightforward installation on excavators, dozers, graders, loaders, ag tractors, or other types of heavy equipment.





Dedicated Power Top-Level Productivity



EWF was developed specifically to increase the power available for your industrial attachments through an independent hydraulic circuit.

Easy to install on a variety of heavy equipment, it is a quick and powerful solution to reach higher level of productivity and profitability.



EWF-100's control panel



EWF-170 and EWF-350's control panel

The power pack is monitored and controlled by the operator through a control panel.

Compact design and straightforward installation on excavators, dozers, graders, loaders, ag tractors, or other types of heavy equipment.

Excavators



Dozers



Graders



Loaders



Ag Tractors



EWF-350

EWF-170

EWF-100

	Engine	350 hp Cummins 8.9 L Turbo	168 hp Cummins 4.5 L Turbo	99 hp Cummins 3.3 L Turbo
	Hydraulic Flow	379 L/min (100 gal/min)	246 L/min (65 gal/min)	170 L/min (45 gal/min)
	Max Hydraulic Pressure	379 bar (5 500 psi)	379 bar (5 500 psi)	379 bar (5 5000 psi)
	Hydraulic tank capacity	133 L (35 gal)	95 L (25 gal)	38 L (10 gal)
	Weight	4 082 kg (9 000 lb)	1 130 kg (2 500 lb)	545 kg (1 200 lb)

These specifications are for information purposes only and are subject to change without notice.



TECHNICAL SPECIFICATIONS

DIMENSIONS AND WEIGHTS	EWF-100	EWF-170	EWF-350
Weight	545 kg (1 200 lb)	1 130 kg (2 500 lb)	4 082 kg (9 000 lb)
Height	112 cm (44 in)	107 cm (42 in)	239 cm (94 in)
Width	142 cm (56.5 in)	122 cm (48 in)	274 cm (108 in)
Depth	68,5 cm (30 in)	130 cm (51 in)	130 cm (51 in)

ENGINE	EWF-100	EWF-170	EWF-350
Model	99 hp Cummins 3.3 L Turbo	168 hp Cummins 4.5 L Turbo	350 hp Cummins 8.9 L Turbo
Number of cylinders	4	4	6
Maximum rpm	2600 rpm	2500 rpm	2100 rpm
Maximum power	99 hp @ 2600 rpm	168 hp @ 2300 rpm	350 hp @ 1800 rpm
Maximum torque	306 lb-ft @ 1600 rpm	459 lb-ft @ 1500 rpm	1120 lb-ft @ 1200 rpm

HYDRAULIC SYSTEM	EWF-100	EWF-170	EWF-350
Hydraulic pressure	379 bar (5 500 psi)	379 bar (5 500 psi)	379 bar (5 500 psi)
Auxiliary pump flow	5 gal/min	25 gal/min	18 gal/min
High flow	170 L/min (45 gal/min)	246 L/min (65 gal/min)	379 L/min (100 gal/min)
Hydraulic tank capacity	38 L (10 gal)	95 L (25 gal)	133 L (35 gal)

COOLING SYSTEM	EWF-100	EWF-170	EWF-350
Engine	Glycol/air	Glycol/air	Glycol/air
Hydraulic	Oil/air	Oil/air	Oil/air

These specifications are for information purposes only and are subject to change without notice.